

I claim:

Sub. a¹ >

1. An improved controller of the type held in two hands simultaneously for controlling electronic imagery, said controller including a housing, a plurality of depressible surfaces at least in-part exposed on said housing with the depressible surfaces acting on electricity manipulating devices contained within said housing and controlled by depression of said depressible surfaces for manipulating electrical outputs at least useful for controlling electronic imagery; wherein the improvement comprises;

at least one of said electricity manipulating devices is a pressure-sensitive variable-conductance sensor for creating an analog electrical output proportional to varying physical pressure applied to at least one depressible surface of the plurality of depressible surfaces;

means for outputting to an image generation machine a signal at least representational of said analog electrical output, whereby a user of said controller may be provided proportional control of action intensity of electronic imagery.

Sub. B³ >

2. An improved controller in accordance with claim 1 wherein the controller has only a single said housing, said housing structured to be held by two hands simultaneously.

Sub. a² >

3. An improved controller in accordance with claim 2 wherein at least four of said electricity manipulating devices are pressure-sensitive variable-conductance sensors for creating said analog electrical output proportional to varying physical pressure applied to at least four of said depressible surfaces of said plurality of depressible surfaces.

Sub. B5 >

4. An improved controller in accordance with claim 3 wherein said at least four of said depressible surfaces comprises a four-way rocker having four codependant areas with each one of said areas positioned over one each of
- 5 said four electricity manipulating devices, one said area per one said electricity manipulating device.

Sub. a3 >

5. A game controller structured to be held by a user in two hands simultaneously, said controller comprising:
- a housing;
- 10 a plurality of depressible surfaces exposed on said housing and depressible by digits of the user's hands to operate
- electricity manipulating devices contained within said housing and operated for manipulating electrical
- 15 outputs of said electricity manipulating devices by depression of said depressible surfaces; at least one of said electricity manipulating devices including
- means for creating an analog electrical output proportional to varying physical pressure applied by at
- 20 least one depressible surface of the plurality of depressible surfaces;
- means for outputting to an image generation machine a signal at least representational of said analog electrical output, whereby a user of said controller may be provided
- 25 proportional control of action intensity of electronic imagery.

Sub. B7 >

6. A game controller in accordance with claim 5 wherein the controller has only a single said housing, said housing structured to be held by two hands
- 30 simultaneously.

Sub. a4 >

7. A game controller in accordance with claim 6 including at least four of said electricity manipulating devices including means for creating said analog

039450 100497

Sub. B97

10 Sub. as

at least one said electricity manipulating device

including means for creating an analog electrical output proportional to varying applied physical pressure;

means for outputting to an image generation machine a signal at least representational of said analog electrical
 5 output, whereby a user of said controller may be provided proportional control of action intensity of electronic imagery.

10. A game controller in accordance with claim 9 including at least four of said electricity manipulating
 10 devices including means for creating said analog electrical output proportional to varying physical pressure applied by at least four of said depressible surfaces of said plurality of depressible surfaces.

Sub. B115 11. A game controller in accordance with claim 10
 15 wherein said at least four of said depressible surfaces comprises a four-way rocker having four codependant areas with each one of said areas positioned over one each of said four electricity manipulating devices, one said area per one said electricity manipulating device.

20 12. An improved method of using a game controller of the type structured to be held by a user in two hands simultaneously, the controller connected to an image generation machine connected to a visual display, in which a user's hand digits depress surfaces upon a housing of
 25 the controller to manipulate imagery on the display, wherein the improvement includes;

depressing at least one of said surfaces with varying degrees of pressure to manipulate imagery in proportion to the degree of depressive pressure.

30 13. An improved method in accordance with claim 12 further including grasping said housing in each of two hands

004430 100197

simultaneously when depressing at least one of said surfaces.

Sub. 26 >

14. An improved method of controlling action intensity of imagery within a visual display of the type
5 allowing user manipulation of action of imagery within the visual display by way of depressing a depressible surface onto a pressure-sensitive variable-conductance sensor connected to electronics within a housing of a two-hand held controller linked to an image generation machine
10 which in turn is linked to the display; wherein the improvement includes the step

depressing said depressible surface with varying degrees of pressure to vary conductance of said pressure-sensitive variable-conductance sensor for varying the
15 action intensity of the imagery proportional to the degree of depressive pressure.

15. An improved method in accordance with claim 14 further including

grasping said housing in each of two hands
20 simultaneously when depressing at least one of said depressible surfaces.

16. An improved method of manufacturing a two-hand held type controller manufactured by way of assembling into a housing a circuit board including circuitry formed
25 to be at least in-part a component of electricity manipulating devices and applying single digit depressible surfaces in-part exposed on said housing and positioned to be depressed onto said electricity manipulating devices, wherein the improvement comprises;

30 installing into said controller at least one pressure-sensitive variable-conductance sensor for creating an analog electrical output in proportion to pressure applied to at least one of said depressible

2025 RELEASE UNDER E.O. 14176

surfaces;

installing into said controller means for outputting to an image generation machine a signal at least representational of said analog electrical output for
 5 providing a user of the controller proportional control of action intensity of electronic imagery.

17. An improved method of manufacturing a two-hand held type controller in accordance with claim 16 further including forming said housing into a single structure
 10 suitable for being held by two hands of a user simultaneously.

Sub. p. 75 18. An improved method of manufacturing a two-hand held type controller in accordance with claim 17 further including installing into said controller said at least
 15 one pressure-sensitive variable-conductance sensor of a type having a wide variable resistance range as a function of depressive pressure.

19. An improved method of manufacturing a two-hand held type controller in accordance with claim 18 further
 20 including installing into said controller said at least one pressure-sensitive variable-conductance sensor of a type having an active material of tungsten carbide within an elastic binder.

25